

Summit International and associated companies, take pride in decades of experience in manufacturing and supply of oilfield and industrial products to oil & gas companies, rig manufacturers, drilling contractors, casing & service companies, refineries, petrochemical and power generation plants, exploration and production operations, marine industries, engineering & construction companies, and bio-remediation projects for many decades.

We have a proven record servicing domestic and international markets. Our experience and technical knowledge have made us a prime source of supply and service to major companies worldwide. Our close association with manufacturers in various industries in form of "agency" or "preferred account", enables us to offer the most proffessional service to our clients. Our full range of products and services are available to all companies that are searching for the right solution.



## **SUMMIT ENVIRO-CLEAN TOOLS**

## **CATALOG**



Dope & Lube Dispenser

DLD-14

[Page 4]

Thread Cleaner [Page 5]

Spill Vacuum Cleaner [Page 6]
SVC-30

Hose Winder
[Page 7]

Manual Mud Bucket [Page 8] MMD-210-4S

Pneumatic Mud Bucket [Page 9]
PMB-480-4D & PMB-640-6S

Pneumatic Mud Bucket with

Mud Recovery Tool

PMB & MRT

# Dope & Lube Dispenser DLD-14

## **Product Information**

Summit Master Dope & Lube Dispenser Machine, model DLD-14, is a pneumatic operated device capable of dispersing a precise quantity of grease, dope and/or lubrication, uniformly and repeatable, on the entire thread of the tubular tool joint or coupling.

The DLD-14 can be used on the drilling rig floor, shop floor and in tubular production facilities. Dispersing an optimum and consistent amount of grease, dope and/or lubrication is crucial in reaching actual make-up torque requirements as recommended by the tubular manufacturers.

The DLD-14 can be custom made for "low temperature" and "automated" use.

## **Properties**

Part Number: EC-DLD-14

Classification: ATEX zone 2 – EC Ex II 3 DG T6

**Technical Specifications:** 

Tubular range: 2 3/8" to 4 ½" 60.3 to 114.3 mm

5" to 9 5/8" 127.0 to 244.5 mm

extend to 13 3/8" 339.7 mm

Dimensions (HxWxL): 35.5" x 21.5" x 21.5" 900x550x550 mm

Weight: 203 Lbs 92 Kg

**Power Requirements:** 

Electric: 110 V / 60 Hz 230V / 50 Hz
Pneumatic: 17.6 cfm @ 100 psi 500 lpm @ 0.7 MPa

## Recommended Thread Component:

**Summit Enviro Dual Master TJC/TC 580** 



SUMMIT INTERNATIONAL a SITCO ENTERPRISES LLC company Houston Texas USA

tel: +1.281.933.1500 fax: +1.281.933.1760 toll: 1.800.347.6930

803 Park Two Drive Sugar Land, Texas 77478 sales@summititc.com www.summititc.com

## Thread Cleaner TC-7

## **Product Information**

Summit Master Thread Cleaner Machine, model TC-7 is a pneumatic operated device capable of cleaning the pin & box threads of the tubular tool joint or coupling.

The TC-7 uses rotating brushes and a solvent to clean the thread. The waste is recovered through a vacuum pressure inside the tank, where the dirty solvent is passed through a filter. The filter retains the solids, allowing the solvent to pass to the collection tank for immediate re-use.

The TC-7 closed loop system is the most environmental friendly tool providing economical savings.

## **Properties**

Part Number: EC-TC-7

Classification: ATEX zone 2 – EC Ex II 3 DG T6

**Technical Specifications:** 

Tubular Range: 2 3/8" to 7" 60.3 to 177.8 mm Dimensions (HxWxL): 31.5" x 21.5" x 37.5" 800x550x950 mm

Weight w/Accessories: 330 Lbs. 150Kg

**Power Requirements:** 

Pneumatic: 17.6 cfm @ 100 psi 500 lpm @ 0.7 MPa



## Recommended solvent:

**Summit Master Paraffin Solvent MPS-400** 



SUMMIT INTERNATIONAL a SITCO ENTERPRISES LLC company Houston Texas USA

## Spill Vacumm Cleaner SVC-30

## **Product Information**

Summit Master Spill Vacuum Cleaner, model SVC-30, is a mechanical device using a pneumatic vacuum pump to suck-up drilling mud, completion fluids and other spills. The SVC-30 provides additional protection to the environment as well as safety by reducing slippage in the work area. The unit is equipped with an automatic shut-off, when the tank reservoir is full.

The SVC-30 can be used on the rig floor, substructures and any other surfaces in the work environment.

The SVC-30 can be enhanced by using it in combination with the vertical hose winder, model HW-SVC-2.

## **Properties**

Part Number: EC-SVC-30

Classification: ATEX zone 2 – EC Ex II 3 DG T6

**Noise Level:** 76.2 dBA measured with a Phonometer at

1 meter (3 feet) distance from the

SVC-30

#### **Technical Specifications:**

Vacuum Air Flow: 120 scfm 3400 lpm 500 mBar Vacuum Level: 15 inHg 825 mBar 24.4 in Hg (upon request): 30 gal 110 ltr Tank Capacity: 2" 50 mm Suction Hose ID: 53" x 30" x 39.5" 1350 x 760 x 1000 mm Dimensions (HxWxL):

Weight: 375 Lbs 170 Kg

#### Power requirements:

Compressed Air Supply: 87 psi 6 Bar

44 cfm @ 15 inHg 1246 lpm @ 500 mBar 80 cfm @ 24.4 inHg 2266 lpm @ 825 mBar



tel: +1.281.933.1500 fax: +1.281.933.1760 toll: 1.800.347.6930 803 Park Two Drive Sugar Land, Texas 77478

sales@summititc.com www.summititc.com

## Hose Winder HW-SVC-2

## **Product Information**

Summit Master Hose Winder uses compressed air to wind up the 2" suction hose of a stand-alone or of the Spill Vacuum Cleaner, model SVC-30, eliminating loose hoses and improving safety in the work area.

## **Properties**

Part Number: EC-HW-SVC-2

**Stand-Alone Dimension** 

**(HxWxL):** 43" x 30" x 28" 1100 x 760 x 720 mm

In Combination with SVC-30

**Dimension (HxWxL):** 68" x 30" x 39.5" 1725 x 760 x 1000 mm





SUMMIT INTERNATIONAL a SITCO ENTERPRISES LLC company Houston Texas USA

## Manual Mud Bucket MMD-210-4S

## **Product Information**

Summit Master Manual Mud Bucket, model MMB-210-4S, is a compact mud bucket which energizes a seal around the tubular to prevent mud from spilling over the rig floor, providing additional protection to the environment as well as safety by reducing slippage in the work area.

The MMB-210-4S is manually moved around the rig floor.

## **Properties**

Part Number: EC-MMD-210-4S

**Technical Specifications:** 

Tubular Sealing Range: 2 3/8" to 7" 60.3 to 177.8 mm

Unit Capacity: 210 Gal 790 Ltr

Unit Dimensions (HxDia): 40" x 18" 1000 x 460 mm

Weight w/Accessories: 165 Lbs 75Kg

Mud Discharge Diameter: 4" single 100 mm single

Optional 2nd Discharge Exit





SUMMIT INTERNATIONAL a SITCO ENTERPRISES LLC company Houston Texas USA

tel: +1.281.933.1500 fax: +1.281.933.1760 toll: 1.800.347.6930 803 Park Two Drive Sugar Land, Texas 77478

sales@summititc.com www.summititc.com

# Pneumatic Mud Bucket PMB-480-4D & PMB-640-4S

### **Product Information**

Summit Master Pneumatic Mud Bucket, models PMB-480-4D & PMB-640-6S, are self-centering around the tubular and very ergonomically and safe tools for easy non-manual use around the rig floor, providing additional protection to the environment as well as safety by reducing slippage in the work area. A safety line, placed in the door opening will prevent the accidental closing of the unit.

The units energize a seal around the tubular to prevent mud from spilling over the rig floor.

## **Properties**

Part Number: EC-PMB-480-4D

**Technical Specifications:** 

**Tubular Sealing Range:** 2 3/8" to 7" 60.3 to 177.8 mm 1800 Ltr Unit Capacity: 480 Gal 1430 x 610 mm Unit Dimensions (HxDia): 56" x 24" Weight w/Accessories: 330 Lbs 150Kg 100 mm double Mud Discharge Diameter: 4" double 228 mm Door Opening:

Part Number: EC-PMB-640-6S

**Technical Specifications:** 

Tubular Sealing Range:2 3/8" to 7"60.3 to 177.8 mmUnit Capacity:640 Gal2400 LtrUnit Dimensions (HxDia):56" x 31.5"1430 x 800 mm

Weight w/Accessories: 480 Lbs 220Kg

Mud Discharge Diameter: 6" single 150 mm single Door Opening: 13" 330 mm

**Power Requirements:** 

Compressed Air Supply 100 psi 7 Bar 17.6 cfm 500 lpm



SUMMIT INTERNATIONAL a SITCO ENTERPRISES LLC company Houston Texas USA

# Pneumatic Mud Bucket with Mud Recovery Tool

PMB together with MRT (Custom Design)

#### **Product Information**

Summit Master Pneumatic Mud Bucket with Mud Recovery Tool, models PMB together with MRT, provides a complete system to recover waste spillage of drilling mud. The PMB capacity is large enough to collect a complete volume of mud up to a triple-stand during drilling/tripping operations. The MRT vacuum action will suck the mud out of the triple-stand, giving a proven 5% mud saving. The overall system will be the optimum economical tool protecting the environment while increasing the safety on the rig floor.





## **ABOUT US**

Summit International, an American based company, is a manufacturer and supplier of quality oilfield and industrial products. Our company has proudly provided products and services to oil & gas companies, rig manufacturers, drilling contractors, casing & service companies, refineries, petrochemical and power generation plants, exploration and production operations, marine industries, engineering & contruction companies, and bio-remediation projects for many decades.

## Summit R Work Apparel



## Summit Vault<sup>™</sup> Chemical Injection Systems and Summit Chemicals



# **Summit Oilfield Lubes/Seals and WHM Lubrication Systems**





## Oilfield & Refineries Tools, Equipment, & Technologies









## **SUMMIT INTERNATIONAL**

a SITCO ENTERPRISES LLC company
Houston ◆ Texas ◆ USA
www.summititc.com sales@summititc.com
Tel: +1.281.933.1500 ◆ Fax: +1.281.933.1760
Toll Free: 1.800.347.6930
803 Park Two Drive
Sugar Land, Texas 77478

# Decades of experience in oilfield & industrial manufacturing, supply, and services worldwide



## **SUMMIT INTERNATIONAL**

a SITCO ENTERPRISES LLC company

Houston ♦ Texas ♦ USA

www.summititc.com ♦ sales@summititc.com

Tel: 281-933-1500

Toll Free: 1-800-347-6930

803 Park Two Drive

Sugar Land, Texas 77478